



CPW RETRIEVABLE SQUEEZE PACKER

The CPW Retrievable Squeeze Packer is designed to perform all the tasks required of a retrievable stimulation and work over packer and withstand high pressures from above or below. It can be used in all types of squeeze cementing, fracturing, and acidizing with subsequent testing.

The hydraulically actuated hold down slips and mechanical lower slips are carbide tipped for long and dependable service. The CPW's packing element system is the proven three-section type, but it is heavier and more reliable than packer systems with an integral bypass.

This Kline packer runs with a separate unloader, such as the Locking Compression Unloader, eliminating the possibility of pumping open (which can occur with many equalizing valves).

SIZE	CASING WT.	GAGE & GUIDE RING OD	PACKING ELEMENT OD	PACKER BORE	CONNECTIONS
4 1/2	9.5-13.5	3.750	3.62	1.94	2 3/8 EU8Rd
4 1/2	13.5-16.6	3.640	3.50	1.94	2 3/8 EU8Rd
5	15-18	4.125	3.94	1.94	2 3/8 EU8Rd
5	11.5-15	4.250	4.12	1.94	2 3/8 EU8Rd
5 1/2	17-23	4.500	4.38	1.94	2 3/8 EU8Rd
5 1/2	14-17	4.641	4.50	1.94	2 3/8 EU8Rd
5 1/2	13-15.5	4.781	4.69	1.94	2 3/8 EU8Rd
5 1/2	14-17	4.641	4.50	1.94	2 7/8 EU8Rd
5 1/2	13-15.5	4.781	4.69	1.94	2 7/8 EU8Rd
6 5/8	20-24	5.750	5.56	2.5	2 7/8 EU8Rd
7	29-38	5.750	5.56	2.5	2 7/8 EU8Rd
7	23-29	5.970	5.75	2.5	2 7/8 EU8Rd
7	17-23	6.188	6.12	2.5	2 7/8 EU8Rd
7 5/8	43-47	6.188	6.12	2.5	2 7/8 EU8Rd
7 5/8	33-39	6.453	6.12	2.5	2 7/8 EU8Rd
7 5/8	24-30	6.672	6.50	2.5	2 7/8 EU8Rd

All dimensions listed in inches.

Larger sizes are available.

Special sizes available upon request.