

## CREST III PACKER

Kline's Crest III Packer is a weight set service packer for high-pressure remedial work such as acidizing, fracturing and squeeze cementing. It sets with minimal tubing manipulation and will withstand differential pressure from above or below.

When set, a balance piston is actuated as pressure increases, exerting downward force on the inner mandrel, thus insuring the equalizing valve is not pumped open.

A large integral fluid bypass allows the packer to be run quickly with minimal chance of swabbing off packing elements or dulling hold down slips. No rotation is required to retrieve the tool, and its equalizing valve opens with the first upward movement.

Standard equipment includes carbide tipped hold down slips, lower slips and drag blocks.

SIZE	CASING WT.	GAGE & GUIDE RING OD	PACKING ELEMENT OD	PACKER BORE	CONNECTIONS
3 1/2	7.7-9.3	2.781	2.75	1.25	1.900 EU10Rd
4	9.5-11.0	3.281	3.25	1.50	2 3/8 EU8Rd
4 1/2	13.5-16.6	3.750	3.62	1.88	2 3/8 EU8Rd
5	15-18	4.125	3.94	1.88	2 3/8 EU8Rd
5	11.5-15	4.250	4.12	1.88	2 3/8 EU8Rd
5 1/2	17-23	4.500	4.38	2.00	2 3/8 EU8Rd
5 1/2	14-17	4.641	4.50	2.00	2 3/8 EU8Rd
5 1/2	13-15.5	4.781	4.69	2.00	2 3/8 EU8Rd
6 5/8	20-24	5.687	5.56	2.50	2 7/8 EU8Rd
7	29-38	5.687	5.56	2.50	2 7/8 EU8Rd
7	23-29	6.000	5.75	2.50	2 7/8 EU8Rd
7	17-23	6.180	6.12	2.50	2 7/8 EU8Rd
7 5/8	43-47	6.180	6.12	2.50	2 7/8 EU8Rd
7 5/8	33-39	6.453	6.12	2.50	2 7/8 EU8Rd
7 5/8	24-30	6.672	6.50	2.50	2 7/8 EU8Rd

*All dimensions listed in inches.*

*Larger sizes are available.*

*Special sizes available upon request.*

